SAFETY DATA SHEET



1. Identification

4700 - 4800 Series Products (Nochek®, Parafflex®, Astorlite®) **Product identifier**

Other means of identification See page 8

SDS number 4700 - 4800 Series (928749)_USA_English

Recommended use Various end uses e.g. additional processing, candles, tire and rubber additives, adhesives, food

contact coatings etc.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name The International Group Inc.

Address 50 Salome Dr.

Toronto

ON, M1S2A8, CA

Telephone 001-(416)-293-4151

E-mail

Contact person

001-(416)-293-4151 **Emergency phone number**

001-(800)-561-3509

CHEMTREC (North

Amerca)

001-(800)-424-9300

2. Hazard(s) identification

Not classified. Physical hazards Not classified. **Health hazards OSHA** defined hazards Not classified.

This product does not meet the criteria for classification according to OSHA Hazard Communication Standard (OSHA GHS).

Label elements

None. **Hazard symbol** Signal word

Hazard statement The product does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Wash hands after handling. Response

Store away from incompatible materials. Storage

Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

The manufacturer lists no ingredients as hazardous according to OSHA 29 CFR 1910.1200.

4. First-aid measures

Inhalation Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to

fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten

material adhering to skin as quickly as possible with water, and see a physician for removal of

adhering material and treatment of burn.

4700 - 4800 Series SDS US 1/8

928749 Version #: 01 Revision date: -Issue date: 16-August-2015 Eye contact

Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention if irritation develops and persists.

Ingestion

Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

Eye and skin contact: When heated, contact with molten product can cause injury and burns.

Indication of immediate medical attention and special Provide general supportive measures and treat symptomatically.

treatment needed General information

If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water on molten material: Explosion hazard could result.

Specific hazards arising from the chemical

By heating and fire, irritating vapors/gases may be formed. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, state and federal laws.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with water.

Small Spills: Where possible allow molten material to solidify naturally.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

2/8

4700 - 4800 Series SDS US

928749 Version #: 01 Revision date: -Issue date: 16-August-2015

7. Handling and storage

Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

8. Exposure controls/personal protection

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles. Wear a face shield when working with molten material.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection

Other

The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory

gear is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Slabs, prills, pastilles or granules

Color White to dark amber.

Odor None.

Odor threshold No data available.

pH Not applicable.

Melting point/freezing point 114.8 - 257 °F (46 - 125 °C)

> 572 °F (> 300 °C)

Initial boiling point and boiling range

012 1 (000 0

Flash point > 374.0 °F (> 190.0 °C) ASTM D-93

Evaporation rate < 0.01 (Butyl acetate = 1)

Flammability (solid, gas) Will support a flame above flash point.

 4700 - 4800 Series
 SDS US

 928749
 Version #: 01
 Revision date: Issue date: 16-August-2015
 3 / 8

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

No data available.

Flammability limit - upper

(%)

No data available.

0.9 % v/v Explosive limit - lower (%) 7 % v/v Explosive limit - upper (%)

< 0.01 mm Hg (77 °F/25 °C) Vapor pressure

Vapor density > 5 (Air = 1)

0.9 - 0.95 (77 °F/25 °C) Relative density

Solubility(ies)

Solubility (water) < 0.1 % (68 °F/20 °C) Partition coefficient No data available.

(n-octanol/water)

No data available. **Auto-ignition temperature Decomposition temperature** No data available. No data available. **Viscosity**

Other information

Partition coefficient

(oil/water)

< 0.01

< 1 % v/v Percent volatile

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Conditions to avoid

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Decomposition of this product can generate carbon dioxide, carbon monoxide and other products

such as aldehyldes and ketones depending on conditions of oxidation.

11. Toxicological information

Information on likely routes of exposure

Inhalation Not relevant at normal room temperatures. When heated, irritating vapors may be formed. Wax

fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

Skin contact Health injuries are not known or expected under normal use. Molten material will produce thermal

Health injuries are not known or expected under normal use. Molten material will produce thermal Eye contact

burns.

Health injuries are not known or expected under normal use. Contact with hot material can cause Ingestion

thermal burns which may result in permanent damage.

Symptoms related to the physical, chemical and toxicological characteristics Eye and skin contact: Contact with molten material may cause thermal burns.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation Thermal burn hazard - contact with hot material may cause thermal burns.

Serious eye damage/eye

irritation

4700 - 4800 Series

Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.

SDS US

Respiratory or skin sensitization

Not classified. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Not classified. Germ cell mutagenicity

928749 4/8

Version #: 01 Revision date: -Issue date: 16-August-2015 Carcinogenicity Not expected to be hazardous by OSHA criteria.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Not classified.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Solid product: Not likely, due to the form of the product.

Chronic effects Not expected to be hazardous by OSHA criteria. Exposure to vapors, fumes, or smoke from

molten material handled in confined areas can produce irritation of respiratory tracts, and possible

physical discomfort to sensitive individuals.

Further information None.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

The product is insoluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

General information This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a

class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III

5/8

(Polyolefinic blend).

4700 - 4800 Series SDS US

928749 Version #: 01 Revision date: - Issue date: 16-August-2015

15. Regulatory information

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

4700 - 4800 Series SDS US

928749 Version #: 01 Revision date: - Issue date: 16-August-2015

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

16-August-2015

Revision date Version # 01

HMIS® ratings Health: 0

Flammability: 1 Physical hazard: 0

NFPA ratings



Disclaimer

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

4700 - 4800 Series SDS US

928749 Version #: 01 Revision date: -Issue date: 16-August-2015 7/8

PRODUCT NUMBER	PRODUCT NUMBER	
4706A	4820B	R-6345B
4706B	4822A	R-6480A
4708A	4824A	1 (0 100) (
4709A	4825A	
4713A	4826A	
4719A	4828A	
4721A	4829A	
4723A	4831A	
4727A	4832A	
4729A	4833A	
4731A	4834A	
4734A	4836A	
4738A	4837A	
4738B	4838A	
4739A	4839A	
4741A	4841A	
4741S	4842A	
4744A	4843A	
4750A	4844A	
4752A	4848A	
4753A 4754A	4848B 4848C	
4756A	4848D	
4757A	4848E	
4758A	4849A	
4760A	4850A	
4761A	4850B	
4765A	4850C	
4766A	4850E	
4766B	4858A	
4769A	4862A	
4769B	4864A	
4773A	4867A	
4777A 4783A	4869A 4870A	
4784A	4872A	
4786A	4874A	
4786B	4875A	
4786D	4876A	
4787A	4877A	
4789A	4878A	
4791A	4879A	
4793A	4891A	
4794A	4892A	
4796A	4895A	
4797A	R-5825A	
4797B	R-5825B	
4798A	R-5915A	
4801A 4802A	R-6049A R-6059A	
4807A	R-6084A	
4809A	R-6136A	
4813A	R-6171B	
4816A	R-6171C	
4818A	R-6209A	
4818B	R-6236A	
4819A	R-6277A	
4819B	R-6340C	
4820A	R-6345A	1

4700 - 4800 Series SDS US 928749 Issue date: 16-August-2015