## THE INTERNATIONAL GROUP, INC.

85 Old Eagle School Road · P.O. Box 384 · Wayne, PA 19087 · (610) 687-9030 · Fax (610) 254-8548 50 Salome Drive · Agincourt, Ontario, Canada M1S 2A8 · (416) 293-4151 · Fax (416) 293-0344

## PARAFFLEX 4630A (Harmony Blend) Product Information Sheet

Product Description	<b>PARAFFLEX 4630A</b> is a specialty wax blend for "one pour" container candle applications
Typical Properties	Congealing Point (ASTM D938): 119°F (48.0°C) Needle Penetration (ASTM D1321 @77°F): 115 dmm typical Color (ASTM D156): +8.0 Appearance (solid): soft, smooth, opaque
Benefits	<ul> <li>Good single pour properties under optimal conditions for containers up to 24 oz. jars</li> <li>Good adhesion to jars under optimal conditions</li> <li>High fragrance load</li> <li>Smooth and creamy look</li> <li>Candles will not creep or slump at temperatures up to 104°F (40°)</li> <li>Pre-blended; no additives required</li> </ul>
Guidelines	<ul> <li>Pouring temperature should be from 160-180°F (71-82°C)</li> <li>Preheat jars to 125° for better adhesion to glass</li> <li>Fragrance oil retention of up to 10% by weight is possible</li> <li>Also reference "General Guidelines for Container Candles" by IGI.</li> <li>Evaluate wicks for each different fragrance-dye combination. The addition of a fragrance and dye to a candle blend changes the wicking properties of the wax, often requiring adjustment of wick size to obtain optimal burning.</li> </ul>
Packaging, Product Form, and Storage Conditions	PARAFFLEX 4630A is available packaged in 10 lb slabs in cartons and as bulk liquid.
Technical Assistance and Customer Support	United States: The International Group Inc 85 Old Eagle School Road Wayne, PA 1-800-852-6537 <b>Canada:</b> The International Group, Inc 50 Salome Drive Toronto, Canada M1S 2A8 1-800-561-3509

## WARRANTY DISCLAIMER STATEMENT

The information contained in this bulletin is based on tests which are believed to be reliable. As actual conditions of use may vary and are beyond the control of THE INTERNATIONAL GROUP, INC. the product's specified characteristics cannot be guaranteed and are offered solely for the buyers evaluation and verification. There are no warranties, representations or continuous, expressed or implied, of any kind, including, but limited to, merchantability or fitness for a particular purpose made by THE INTERNATIONAL GROUP, INC. or its officers, employees or affiliates, in connection with the sale of the products described in this bulletin. Accordingly, the purchaser and each user assumes all risks and liability in connection with the sale of the products described in the process os as to infinge or conflict with any patent. Further, it is the user's obligation to utilize this material in full complicace with health, safety and environmental regulations. THE INTERNATIONAL GROUP, INC. crecommends that the Material Safety Data Sheet for this product be consulted prior to handling.