

Stainless Steel Wax Melter 19 lb.

Safety Information

- This product is intended for household or similar use only. Do not use the appliance for any purpose other than its intended use.
- Do not remove the insulated sleeve while using the melter or until the melter cools.
- Always ensure the tap lever is in the OFF position (facing left) before use to avoid unwanted spills.
- Keep the lid on while the melter is in use.
- Do not leave the melter unattended while in use. Keep away from children and pets.
- To prevent damage to the melter when cleaning, do not use alkaline cleaning chemicals or other harsh detergents when cleaning. Use a soft cloth and mild detergent or isopropyl alcohol.
- Do not attempt to replace a damaged cord. It must be replaced by the manufacturer or other qualified parties.
- The melter and any metal surfaces will be hot while in use and immediately thereafter. Take caution while handling.
- Do not operate the melter when empty. The melter must always be filled with wax above the MIN line when operating.
- In case of wax clogging the tap, use a heat gun set at a low temperature to restore flow.

How to Use

1. Prior to filling the melter, make sure the melter tap is closed by turning the tap lever to the left.
2. Remove the lid and add the desired quantity of wax to the melter. The wax fill must be above the MIN line and below the MAX line. Place the lid on the melter.
3. Plug in the melter. Turn the thermostat to the desired temperature. The indicator light will turn on as the melter begins to heat. Note: During the heat cycle, the indicator will turn on and off throughout the melting process to achieve your desired temperature.
4. It will take between 30 and 90 minutes for your wax to melt depending on the type and hardness of your wax and the amount used.
5. When the bottom of the pot reaches the desired temperature, the melter will pause heating and the indicator light will turn off. After approximately 2-3 minutes, the melter will begin heating again and the indicator light will turn on.
6. Allow the melter to continue the heating cycle until the wax has fully melted.
7. To dispense melted wax, place a metal pouring pitcher under the tap. Turn the tap lever to the right to begin the flow. Turn the lever to the left to stop dispensing wax. CAUTION: The melter and wax will be hot.
8. When finished, turn the thermostat to the OFF position and unplug the melter.

Cleaning

1. Remove any remaining wax from the melter by pouring it out or wiping the wax out of the machine. Avoid scraping or prying solid wax out of the melter to prevent damage.
2. Prior to washing, ensure the melter is unplugged and has cooled completely.
3. Wash thoroughly with hot water and a mild, non-abrasive detergent. Isopropyl alcohol and a soft cloth may also be used to clean the interior of the melter. CAUTION: Do not submerge the melter in water.
4. Use a washing pad or sponge to carefully remove any remaining residue. Do not use steel wool or coarse scouring pads, as these may damage the melter's surface.
5. Rinse out with hot water.
6. Dry the melter thoroughly using a soft cloth before and after use.

For support, please go to support.candlescience.com.